

'SN' SERIES BALL VALVE



Ball Valves 6,000 PSI

The single nut mounted ball valve is rated from vacuum up to 6,000psi. The single nut allows fast panel mounting. Max panel thickness is 11mm (dependant on valve size). A heavy duty yet compact design offering easy installation and maintainability.

DESIGN FEATURES

<ul style="list-style-type: none">• Flexible 3 piece design for easy maintenance.	<ul style="list-style-type: none">• Temperature range -40°C to 150°C as standard (other temperatures available on request)
<ul style="list-style-type: none">• Bi-directional floating ball design to ensure leak-proof shut-off on pressure or vacuum.	<ul style="list-style-type: none">• Choice of end connections including NPT, BSPP, BSPT and twin ferrule compression ends.
<ul style="list-style-type: none">• 90 degree low torque operation.	<ul style="list-style-type: none">• Choice of handle types. Mazak pointer handle as standard, to indicate direction of flow.
<ul style="list-style-type: none">• Single nut mounting facility for ease of installation.	<ul style="list-style-type: none">• Full material traceability.
<ul style="list-style-type: none">• Choice of ball and stem materials such as 316ss / Duplex / Monel	<ul style="list-style-type: none">• Materials of construction can be supplied to meet the requirements of NACE MR -0175 latest revision.
<ul style="list-style-type: none">• Repair kits available should the valve need servicing to prolong its life.	

